

## 要項表

形式		容量(Ah) 5時間率	外形図	外形寸法(約mm)				液面線高さ(約mm)		質量 (約kg)	電解液量 (約リットル)
ベント形	シール形			W	L	H(最大)		A	B		
						ベント形	シール形				
AMH20P	AMH20PE	20	(1)	143	*52	272	332	183	30	2.6	0.9
AMH30P	AMH30PE	30	(1)	143	*52	272	332	183	30	2.9	0.8
AMH40P	AMH40PE	40	(1)	143	*52	272	332	183	30	3.1	0.7
AMH50P	AMH50PE	50	(1)	143	*52	272	332	183	30	2.9	0.5
AMH60P	AMH60PE	60	(1)	143	76	272	332	183	30	4.5	1.1
AMH80P	AMH80PE	80	(1)	143	76	272	332	183	30	5.2	1
AMH100P	AMH100PE	100	(1)	145	100	272	332	183	30	6.3	1
AMH120P	AMH120PE	120	(1)	145	100	272	332	183	30	7	0.9
AMH150P	AMH150PE	150	(4)	170	120	370	441	245	40	11	3
AMH200P	AMH200PE	200	(6)	170	120	370	441	245	40	12.5	2.3
AMH250P	AMH250PE	250	(6)	170	195	370	441	245	40	18	5.2
AMH300P	AMH300PE	300	(6)	170	195	370	441	245	40	19.5	4.7
AMH350P	AMH350PE	350	(7)	170	195	370	441	245	40	20	4.3
AMH400P	AMH400PE	400	(7)	170	195	370	441	245	40	21.5	3.6
AMH450P	AMH450PE	450	(7)	170	285	370	441	245	40	29	7.5
AMH500P	AMH500PE	500	(8)	170	285	370	441	245	40	31.5	6.4
AMH600P	-	600	(8)	170	390	370	-	245	40	39	10
AMH700P	-	700	(8)	170	515	372	-	245	40	50	15
AMH800P	-	800	(8)	170	515	372	-	245	40	53	14
AMH900P	-	900	(8)	170	515	372	-	245	40	56	13
AMH1000P	-	1000	(8)	170	515	372	-	245	40	58	12

\*シール形の長さ寸法は52にセル間隔5を加え合計57となります。