

要項表(単電池)

HS-(E)形(高率放電用ペースト式)

形式	公称電圧 (V)	容量(Ah)		外形寸法(約mm)				液面線高さ(mm)		質量 (液を含む 約kg)	電解液量 (約リットル)
		1時間率 (定格)	10時間率 (参考)	W	L	H(最大)		A	B		
						ベント形	触媒栓式				
HS-30-6(E)	6	18	30	132	200	230	260	150	10	9	2.6
HS-40-6(E)	6	24	40	132	200	230	260	150	10	10	2.4
HS-50-6(E)	6	30	50	132	200 (252)	230	260	150	10	11 (12)	2.3 (3)
HS-60-6(E)	6	36	60	132	252 (303)	230	260	150	10	13.5 (15)	3 (3.5)
HS-80-6(E)	6	48	80	132	303 (472)	230	260	150	10	16.5 (18)	3.6 (6)
HS-100-6(E)	6	60	100	132	472	230	260	150	10	23	5.8
HS-120-6(E)	6	72	120	132	472	230	260	150	10	24.5	5.6
HS-30(E)	2	18	30	132	67	230	260	150	10	3	0.9
HS-40(E)	2	24	40	132	67	230	260	150	10	3.5	0.8
HS-50(E)	2	30	50	132	67 (102)	230	260	150	10	4 (4.5)	0.8 (1)
HS-60(E)	2	36	60	132	102	230	260	150	10	5	1.2
HS-80(E)	2	48	80	132	102 (154)	230	260	150	10	6 (7)	1.2 (2)
HS-100(E)	2	60	100	132	154	230	260	150	10	7.5	1.9
HS-120(E)	2	72	120	132	154	230	260	150	10	8.5	1.9
HS-150(E)	2	90	150	170	120	380	420	285	10	13.5	3.8
HS-200(E)	2	120	200	170	120	380	430	285	10	15	3.6
HS-250(E)	2	150	250	170	120	380	430	285	10	16.5	3.5
HS-300(E)	2	180	300	170	195	380	430	285	10	23	6.5
HS-400(E)	2	240	400	170	195	380	430	285	10	26	6
HS-500(E)	2	300	500	170	285	380	430	285	10	35.5	9
HS-600(E)	2	360	600	170	285	380	430	285	10	38.5	8.5
HS-700(E)	2	420	700	170	390	380	430	285	10	49	13
HS-800(E)	2	480	800	170	390	380	430	285	10	52.5	12.5
HS-900(E)	2	540	900	170	390	380	430	285	10	55	12
HS-1000(E)	2	600	1000	170	515	380	430	285	10	68	16
HS-1200(E)	2	720	1200	170	515	380	430	285	10	74	15.5
HS-1500(E)	2	900	1500	653	280	425	560	293	10	125	39
HS-2000(E)	2	1200	2000	653	280	425	560	293	10	141	36
HS-2500(E)	2	1500	2500	653	280	425	560	293	10	157	34

注:()内の数値は液中比重計付の場合を示します。